

Heavy Duty Incremental Encoders

Features

A heavy-duty encoder is the most rugged encoder you can buy. Top-of-the-line bearings allow a service life of 12 billion revolutions. Features include:

- 10 mm standard shaft
- Rugged body with 78 mm diameter and 60 mm depth
- Splash-proof IP65 rating
- Incremental operation from 30 pulses per revolution to 5,000 pulses per revolution
- 100 kHz maximum response frequency
- 10-30 VDC, Totem-pole output



Standard shaft (TRD-GK) model

Note: Yellow shaded part numbers are non-stock. Availability may range from four to six

Heavy Duty Standard Shaft Incremental Encoders					
Model	Price	Pulses per Revolution	Input Voltage	Output	Body Diameter
TRD-GK30-RZD	<--->	30	10-30 VDC	Totem-pole (sink/source)	78mm
TRD-GK100-RZD	<--->	100			
TRD-GK120-RZD	<--->	120			
TRD-GK200-RZD	<--->	200			
TRD-GK240-RZD	<--->	240			
TRD-GK250-RZD	<--->	250			
TRD-GK300-RZD	<--->	300			
TRD-GK360-RZD	<--->	360			
TRD-GK400-RZD	<--->	400			
TRD-GK500-RZD	<--->	500			
TRD-GK600-RZD	<--->	600			
TRD-GK800-RZD	<--->	800			
TRD-GK1000-RZD	<--->	1000			
TRD-GK1200-RZD	<--->	1000			
TRD-GK1500-RZD	<--->	1500			
TRD-GK1800-RZD	<--->	1800			
TRD-GK2000-RZD	<--->	2000			
TRD-GK2500-RZD	<--->	2500			
TRD-GK3600-RZD	<--->	3600			
TRD-GK5000-RZD	<--->	5000			

Electrical Specifications		
Model		TRD-GKxxx-RZD
Power Supply	Operating Voltage	10 - 30VDC*
	Allowable Ripple	3% rms max.
	Current Consumption	At less than 16VDC: 50 mA max. / at 16VDC or more: 70mA max.
Output Waveform	Output Signal	Two phase + home position
	Duty Ratio	50 ± 25%
	Max. Frequency Response	100kHz max.
	Signal Width at Home Position	At 400P or less: 25 to 150%; at 500P or more: 1° at 30°
	Rise/Fall Time	2µs max. (when cable length is 2m or less)
Output	Output Type	Totem-pole
	Current: Outflow: H	30mA max.
	Voltage: H	(power source voltage - 4V) min.
	Voltage: L	2V max.
	Load Power Voltage	35VDC max.
* To be supplied by Class II source		
Mechanical Specifications		
Starting Torque	Max. 0.1 Nm (.074 ft lbs) max. at 20°C (68°F)	
Max. Allowable Shaft Load	Radial: 100N (22.48 lbs) Axial: 50N (11.24 lbs)	
Max. Allowable Speed	5,000 rpm	
Service Life of Bearing	12 billion revolutions (at max. allowable speed)	
Wire Size	AWG24	
Weight	Approx. 600g (21.16 oz) with 2m cable	
Environmental Specifications		
Ambient Temperature	10 to 70°C; 14 to 158°F	
Storage Temperature	-25 to 85°C; -13 to 185°F	
Operating Humidity	35-85% RH (with no condensation)	
Insulation Resistance	50MΩ min.	
Vibration Resistance	At 500P or less: Durable for one hour along three axes at 10 to 55 Hz with 0.75 mm amplitude At 600P or more: Durable for one hour along three axes at 10 to 55 Hz with 0.35 mm amplitude	
Shock Resistance	At 500P or less: 11 ms with 980 m/s ² applied three times along three axes At 600P or more: 11 ms with 294 m/s ² applied three times along three axes	
Protection	IP65: dust and splash proof	

