



M-7058



M-7058D

**M-7058/
M-7058D**
8-channel 80-250VAC Isolated Digital Input
Module with 16-bit Counters

Introduction

M-7058 offers 8 channels differential for AC digital input, each of which features photocouple isolation for channel to channel. Its on voltage level lies in 80 V ~ 250 VAC. All DI channels are also able to be used as 16-bit counters. M-7058D has 8 LED indicators for DI channel status. 4kV ESD protection and 5000V intra-module isolation are standard.

Features

- AC Digital Inputs
- Differential Inputs
- Photocouple Isolation
- DI Can Be Used As Counters
- 4 kV ESD Protection
- 5000 Vrms Isolation Voltage
- Dual Watchdog
- RoHS Compliance
- Wide Range of Operating Temperature: -25 ~ 75 °C

Specifications

Digital Input	
Channels	8
Input Type	AC, Differential, isolated
Off Voltage Level	30 VAC max.
On Voltage Level	80 ~ 250 VAC
AC Frequency	50 ~ 60 Hz (> 45 Hz Min.)
Input Impedance	68K Ohm, 1W
Counters	channels : 8
	Max. Counts : 16-bit (65535)
	Max. Input Frequency : 100Hz Min. Pulse Width : 5ms
Photo-Isolation	5000 VDC
Interface	
Interface	RS-485
Format	N, 8, 1
Baud Rate	1200 ~ 115200bps
LED Display	
1 LED as Power/Communication indicator	
8 LEDs as Digital Input indicators (for M-7058D)	
Power	
Input Voltage Range	10 ~ 30 VDC
Power Consumption	0.3W (M-7058) / 1.0W (M-7058D)
Protocol	
Support Modbus and DCON Protocol	Yes
Environment	
Operating Temperature	-25 ~ 75°C
Storage Temperature	-40 ~ 85°C
Humidity	5 ~ 95% RH, non-condensing

Ordering information

M-7058 CR	8-channel 80-250VAC Isolated Digital Input Module with 16-bit Counters (RoHS)
M-7058D CR	M-7058 with LED Display (RoHS)